





Ideal for Microbiological Manipulations, Sterility Testing, research work & for general dry-processing work in semiconductor industry etc.

Full Cabinet made from CRCA Steel sheet - powder coat finished. Construction: Standard

> : GMP Full Cabinet made from Stainless Steel (304 Grade).

Working Table Top Made from Stainless Steel (304 Grade).

Side panels Thick transparent Acrylic.

Motor Mounting Unique spring suspension system with bellow which helps to

reduce Vibrations and noise, produced during the process.

HEPA Filter Mini Pleat - High Efficiency Particular Air Filter with

Efficiency 99.97 % down on 0.3 micron.

Pre Filter Washable Filter having efficiency of 95 % down to 10 micron. :

Air Flow Velocity 90 FPM (0.45 m/s) 10 FPM (0.05 m/s) average velocity

measured 6 in (153.4 mm) from the diffused screen.

Air Uniformity ± 20% of average or better.

Balanced blowers fitted with direct driven FHP Motor. Air Circulation

(For Variable air flow speed in accordance with filter loading).

Static Pressure Indicator Oil Filled Manometer.

Inner chamber Sterilization : Through UV Germicidal tube.

Inner chamber Illumination : Fluorescent tube light.

Noise Level :< 65 DB measured at 1 Mtr from filter face.

Gas Cock Provision.

Castor Wheels for easy mobility.

| MODEL | | WORKING AREA (L X W X H) | HEPA FILTER DIMENSIONS | PRE - FILTER | ILLUMINATION |
|------------|--------|-----------------------------|------------------------|--------------|--------------|
| HORIZONTAL | LHLF-1 | 2 X 2 X 2 Feets | 24 X 24 X 6 | 1 NO. | 1 X 20 WATTS |
| | LHLF-2 | 3 X 2 X 2 Feets | 36 X 24 X 6 | 1 NO. | 1 X 20 WATTS |
| | LHLF-3 | 4 X 2 X 2 Feets | 48 X 24 X 6 | 1 NO. | 1 X 40 WATTS |
| VERTICAL | LHLF-4 | 2 X 2 X 2 Feets | 24 X 24 X 6 | 1 NO. | 1 X 20 WATTS |
| | LHLF-5 | 3 X 2 X 2 Feets | 36 X 24 X 6 | 1 NO. | 1 X 20 WATTS |
| | LHLF-6 | 4 X 2 X 2 Feets | 48 X 24 X 6 | 1 NO. | 1 X 40 WATTS |